

CALL FOR CURRENT PRICING

(800) 562-0900

CATALOG #67

BURR KING®

MADE IN USA
SINCE 1951

GRINDING
POLISHING
SURFACE CONDITIONING
DEBURRING
CLEANING
DESCALING
FINISHING



BELT GRINDERS • DISC GRINDERS • POLISHERS
VIBRATORY • SURFACE CONDITIONING EQUIPMENT

WWW.BURRKING.COM • (800)621-2748

INFO@SWIFTTOOL.COM

WWW.SWIFTTOOL.COM

BURR KING®

PROVIDING QUALITY FINISHING PRODUCTS SINCE 1951

Broad Product Line

For over sixty years Burr King grinders, polishers, and vibratory products have been used by the world's leading companies. Our products use innovative designs of uncompromising quality, they are industrial grade, intended for use on metals, wood, composites, plastics, rubber, stone, fiberglass, and other materials. Burr King products are simple-to-use, no nonsense tools preferred by professionals.

Quality first and last

Each Burr King machine, accessory, and consumable is rigorously tested for specification compliance throughout its manufacture. Should we deliver a product that does not function, or meet its intended purpose we will correct the situation without quibbling - guaranteed!

Free tests and evaluations on customer parts

Parts may be sent to the Burr King factory for a full process test report. Customers will receive their processed parts back with a complete, easy to understand finishing recommendation that lists methods, materials, equipment, and time variables. Burr King customers can make informed, low risk buying decisions.

Customer site product trial

Many Burr King products can be brought directly to the customer's plant for demonstration. Where this is not practical any Burr King machine can be delivered to the customer's work site for actual customer trial prior to purchase. Call the Burr King factory for information about this valuable program.

Ready and competent customer service

Our factory personnel, and national product representatives are ready and able to assist customers with applications, service, repair, and/or special situations.

**BURR KING MANUFACTURING Co., Inc.****1220 TAMARA LANE, WARSAW, MO 65355****(660) 438-8998, FAX (660) 438-8991****INFO@BURRKING.COM, WWW.BURRKING.COM**

BURR KING®

“Velvet Touch” Three Wheel Belt Grinders

Burr King's family of three wheel grinders provides maximum versatility. Contact wheel, platen, workrest support, and loose belt grinding are precision controlled with positive belt tracking, quick belt change, and linear belt tension. Constructed of rugged cast aluminum and precision machined components, every Burr King grinder delivers unexcelled grinding performance and reliability.

MODEL 760

CAUTION

USE PROPER EYE,
FACE, HAND AND
BODY PROTECTION
WHEN USING THIS
OR ANY OTHER
GRINDER.



Shown with optional variable speed

72110 shown

- Versatile
- Reliable
- Powerful
- Smooth
- Aggressive
- Heavy Duty

- Rotating parts covered eliminating parts entanglement, greater operator safety
- Deeper horizontal and vertical throat clearance for larger and odd shaped parts
- Improved dust extraction
- New and improved door latching system
- New pinch point guarding when back up platen is removed
- New urethane covered idler wheels for longer life
- New idler wheels are electrostatically conductive

**MODEL 760 IS THE LARGEST EXAMPLE OF OUR VERSATILE
THREE WHEEL BELT GRINDERS.**

**IT OFFERS CONTACT, BACKUP PLATEN, WORKTABLE AND
LOOSE BELT GRINDING AT 8000 S.F.P.M.**

BURR KING®**“Velvet Touch” Three Wheel Belt Grinders****MODEL 482**

STANDARD
48" BELT
UP TO 2" WIDE



40100 shown



- Contact wheel, platen and workrest support grinding
- Slack belt grinding
- Adjustable belt tension
- Positive belt tracking/patented design
- Quick belt change
- Large throat clearance for enhanced work point access
- Variable speed 120/220-1 PH, and 220/440-3 PH options
- Precision machined cast aluminum frame
- Accepts internal grinding attachments (excluding model 562)
- Accepts nylon, buffing, wire, fiber wheels
- Compact footprint friendly to "cell" manufacturing
- OSHA compliant, enclosed guarding

**MACHINE CAN BE PEDESTAL
OR BENCH MOUNTED.**

MODEL 562

STANDARD
42" BELT
UP TO 1" WIDE

Model 562
shown with
optional dust
scoop, (DS-5)
& pedestal.



56100 shown



Model 760 shown
with optional pedestal.

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®**“Velvet Touch” Two Wheel Belt Grinders****MODEL 960-250**

STANDARD
60" BELT
UP TO
2 1/2" WIDE



90100 shown


VERTICAL/HORIZONTAL

Burr King's family of two wheel grinders provides vigorous contact wheel, workrest, and platen grinding in a frame design that pivots to ideal work positions. These machines are frequently selected as tool post grinders, roll grinders, and for fixturing into centerless grinding applications. Available in easily adjusted variable speed and aggressive single speed, 2-1/2" x 60" or 4" x 60" belt models.

- Contact wheel, platen and work support grinding
- Adjustable belt tension
- Positive belt tracking
- Quick belt change
- Up to 8000 SFPM belt speed standard
- Compact footprint friendly to "cell" manufacturing
- Adapts for "tool post" or "on center" grinding
- Adapts for robot mounts
- Variable speed 120/220-1 PH, and 220/440-3 PH options
- Precision machined cast aluminum frame
- OSHA compliant, enclosed guarding

MODEL 960-400

STANDARD 60" BELT
UP TO 4" WIDE



95103 shown

Shown with optional mag starter.

**SURFACE GRINDER
ATTACHMENT NOW AVAILABLE.**

Shown with optional
mag starter.



95103 shown

Easily adjusted vertical or horizontal.

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®

X400 BELT GRINDER

2" X 48" BELT

A PROFESSIONAL GRINDER AT A CONSUMER PRICE!



24820 shown

Burr King Manufacturing is proud to present our addition to the Burr King Family. The X400 not only introduces a new machine, but will be the first of our "Prosumer" line. The Prosumer line is especially designed for professional consumers that border on the line of being consumers and professional users.

We used some of the best features of our Model 760, 960, 482 and engineered a machine just for users like you. The X400 features a 2x48 belt, a powerful 1 HP motor, contact wheel grinding, slack belt grinding, and platen grinding. We also kept our adjustable work rest, so you can get that perfect angle. The X400's belt travels at 90 MPH just like the 760, and the body pivots like the 960.

Don't settle for a cheap import when you can own the best quality machine made in America!

CONTACT WHEEL, SLACK BELT & PLATEN GRINDING

UP TO 8,000 SFPM


MULTIPLE MOTOR CONFIGURATIONS AVAILABLE

- Contact wheel, platen and work support grinding
- Adjustable belt tension
- Positive belt tracking
- Quick belt change
- Up to 8000 SFPM belt speed standard
- Compact footprint friendly to "cell" manufacturing
- Variable speed 120/220-1 PH, and 220/440-3 PH options
- Precision machined cast aluminum frame
- OSHA compliant, enclosed guarding

BURR KING®

BURR KING 'E' MACHINES

ENHANCED GRINDERS AND POLISHERS



7211007 shown

*All the Features of our
Regular Belt Grinder Plus -*

- Variable Speed
- Running Indicator Light
- 30mm Mushroom Stop Button
- Positive Door Guard Switch
- Rapid-Stop Braking Technology
- GFCI Compatible VFD
- Special Drive Firmware



The 760E with Rapid-Stop Braking™ will activate the brake and stop the machine in just seconds when either the red mushroom stop is activated or the door is opened. With the addition of the switch, wired directly to the controller, it prevents operators from leaving the door in an open position while running. The door must be closed to activate the belt grinder.

We understand with a machine that runs as quiet and smooth as a Burr King grinder, sometimes in a shop environment it is nearly impossible to tell if the machine is running or not. The visual run indicator light, located on top of the controller, reduces the chance of an operator leaving the machine running when finished with the operation, or when they leave the working area. The run indicator light can be seen while the whisper of the machine can not be heard.

Most of our other machines we manufacture can also be outfitted with these enhanced features. Please contact your manufacturing representative or Burr King for more information.



9211001 shown

DISC GRINDERS & POLISHING LATHES CAN ALSO BE ENHANCED

NOTICE: It should not be implied that the 760E is a safer machine to operate or to own than the standard belt grinders.

The "Enhanced" incorporates features that Burr King customers have suggested us adding. It must be understood improper uses of any equipment may be dangerous. Please read and understand all operating instructions.

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®

THE KNIFEMAKER'S EDGE! MODEL 960-272

- 8" or 10" Diameter Contact Wheel Available
- Grind, polish, buff with one machine.
- Hollow grind, flat grind, contour, slack belt, vertical or horizontal platens.
- Fixed and variable speeds, smooth running.
- Small wheel attachment.
- Serrated contact wheels for rapid stock removal.

**SURFACE GRINDER
ATTACHMENT NOW AVAILABLE.**



99730 shown
Shown with optional variable speed

**REQUEST FLYER
TO SEE
NEW OPTIONS**



Optional 965 Small Wheel Attachment for 2" wide belts. 5/16" - 1.5" Wheels Inboard and Outboard Bearings Style Attachments Available



Make your Burr King a finishing center. Run buffs, woven and convolute polishing wheels simply by using one of our versatile adapters.



Optional 944 Vertical Platen Attachment with optional workrest.

CAUTION: The Model 960-272 belt grinder is designed by use by persons who require full access to most portions of the belt path. As such users of the 960-272 must exercise caution when using the machine to avoid entanglement in rotating parts, entrapment in pinch points, being struck by grinding debris, being struck by ejected work pieces and other hazards that are associated with power driven rotating equipment. Failure to properly use the machine, follow operating instructions, and good safety practices may lead to serious personal injury, death or property damage. Not for industrial applications. If you require a machine designed for industrial applications please see the Model 960 on page 5.

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®

MODEL 720 PROBE BELT GRINDER

The Model 720 presents a unique up front, two wheel, rear drive configuration that quickly accepts contact wheel finishing diameters from 3/8 inches to 3 inches in diameter. The Model 720 is equipped with a reliable and fully adjustable air pressure, belt tension control system. Using 1/2 inch to 2 inch belt width. The Model 720 72 inch belt track delivers long abrasive life coupled with excellent utility. Available in single or Variable speed. See page 14 for accessory arms.

MODEL 720 PROBE BELT GRINDER DELIVERS MORE UTILITY TO BURR KING CUSTOMERS!


- Reach into deep cavities
- Finish the I.D. of tubing
- Work exotic materials with multiple belt speeds from 500 to 5500 SFPM
- Excellent for turbine blades
- Delicately blend finishes
- Rough away material
- Finish inside diameters

STANDARD FEATURES:

- 72 inch belt track
- 1/2 to 2 inch belt widths (Optional)
- 1 inch diameter x 2 inch wide contact wheel (Standard)
- Standard wheels 3/8 inch to 3 inch
- 5500 SFPM
- 1.5 horse power in popular voltage and phase options
- Air Tension control abrasive belt
- Pressure regulation and adjustment
- Accepts all Burr King 1400 series nose attachments (choice of one with machine)
- Heavy fabricated steel frame
- Out front grinding point with up to 14 inches probe capability (diameter dependent)
- Integrated dust collection shroud with 3 inch outlet
- Belt guard with belt access door
- Bench or pedestal mount
- Foot print approximately 20W x 36D x 36H

OPTIONAL FEATURES:

- Variable speed from 500 to 5500 SFPM in 1 phase and 3 phase options
- Magnetic starters
- 2 horse power motors
- Mounting pedestal
- Various nose attachments with contact wheels from 3/8 to 3 inches in diameter with 1/2, 1, and 2 inch widths (See Factory for larger wheels and sizes)



16110 shown

Shown with optional variable speed.



ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®

MODEL 979


3" X 79" BELT GRINDER

This aggressive belt grinder features a 3 x 79 inch belt track with heavy steel construction to deliver material finishing with the quiet, smoothness that customers expect from a quality grinding machine year after year.

- 3" x 79" belt track
- 7200 surface feet per minute (SFPM) belt speed
- 3 or 5 horsepower American made motors
UL/CSA variable speed option available
- Swing frame grinding option
- Heavy welded steel construction
with cast iron accessories
- 8" diameter 70 durometer serrated contact
wheel with deep groove sealed ball bearings
- Integrated, heavy steel pedestal
with optional elevation control
- Ventilated 4" x 18" steel platen
- 3" Hose Outlet



Optional
Magnetic
starter and
elevation
control.



Model 979 adapts as a swing grinder.

SAFE

- O.S.H.A. compliant belt track and pinch points guarding
- UL/CSA motors and electrical controls

OPERATOR & SHOP FRIENDLY

- Quick easy belt change with positive simple belt tracking control
- Quiet smooth running minimizes operator fatigue
- Small footprint uses less shop space

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®

WET GRINDERS 2.5" OR 4" WIDE

**IDEAL FOR LAPIDARY, GLASS, AND
OTHER FINISHING APPLICATIONS
OPTIMIZED BY DIAMOND ABRASIVES!
WITH DIAMOND BELTS YOU WILL EXPERIENCE
UP TO 100 TIMES THE LIFE OF EXPECTANCY
OF SILICON CARBIDE ABRASIVES WHILE
ATTAINING VASTLY SUPERIOR RESULTS!**

- 5000 surface feet per minute to optimize modern diamond abrasives
- 960-401 features 4 x 60 inch belt track
- 960-251 features 2-1/2 x 60 inch belt track
- Integrated water fed system including pump, water flow adjusting valve, dual 120 degree spray nozzles, stainless steel water receiver tray with drain, sump, and interconnecting flexible tubes
- 1HP NEMA 4x motor and switch for wet application
- Ground fault interrupter power distribution "rain" box with master switch for the grinder and feeder pump for maximum safety in wet grinding modes
- Cast aluminum frame for Burr King ruggedness
- Safe belt track guarding that is OSHA compliant
- Bearings are high quality and sealed for life
- Belt change is quick with a linear belt tension device
- Belt tracking is simple and effective
- Work position is adjustable from horizontal to vertical
- Platen is full belt and generously long
- Contact wheel, slack, or platen grinding
- Dry grinding is as simple as turning off the pump
- GFCI compatible variable speed control
- One year, limited warranty
- Made in the USA



31100 shown

*Shown with optional variable speed.
(Pedestal included)*

SumpPak 1000 filtration system and pedestal are included (Shown).


BURR KING®

STANDARD BELT GRINDER SPECIFICATIONS

For optional features & specifications consult factory.

	Model 760	Model 960	Model 482	Model 562	Model 979	Model 720	Model 960 Wet Grinder	Model X400
Abrasive Belt Size	1-1/2" x 2" x 60"	2-1/2" or 4" x 60"	2" x 48"	1" x 42"	3" x 79"	1" to 2" x 72"	2-1/2" or 4" x 60"	2" x 48"
Abrasive Belt Speed (upto)	8000 SFPM	8000 or 6500 SFPM	6000 SFPM	5600 SFPM	7200 SFPM	5500 SFPM	5000 SFPM	8000 SFPM
Throat Clearance	8-7/8"	None	7-1/2"	5-1/2"	None	None	None	4"
Contact Wheel Dimensions	7" x 1-1/2" or 7" x 2"	7" x 2-1/2" or 7" x 4"	5" x 2"	4-3/4" x 1"	8" x 3"	1/2" x 1" - 2" x 3"	7" x 2-1/2" or 7" x 4"	7" x 2"
Contact Wheel Hardness (Optional 90 Duro)	55 Durometer	55 Durometer	55 Durometer	55 Durometer	70 Durometer	70 Durometer	55 Durometer	55 Durometer
Belt Tension, Quick Change Assembly	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Positive Belt Tracking Adjustment	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Overall Height x Width x Depth	26" x 24" x 23"	30" x 21" x 30"	21" x 20" x 19"	20" x 17" x 15"	48" x 26" x 44"	36" x 20" x 36"	16" x 22" x 30"	28" x 20" x 18"
Safety Belt Guard	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Base Area	10" x 13"	8-1/2" x 8"	10" x 13"	10" x 13"	18" x 18"	8-1/2" x 8"	8 1/2" x 8"	10" x 13"
Steel Backup Platen	2" x 6" x 1/4"	2-1/2" x 8" 4" x 14"	2" x 6" x 1/8"	1-1/8" x 5" x 1/8"	4" x 18"	None	2-1/2" x 8" 4" x 13"	2" x 6" x 1/4"
Adjustable Workrest	Yes	Yes	Yes	Yes	Yes	None	Yes	Yes
Construction	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Fabricated Steel	Fabricated Steel	Cast Aluminum	Cast Aluminum
Estimated Shipping Weight	105 - 135 lbs	95 - 145 lbs	80 - 105 lbs	75 - 100 lbs	375 lbs	180 - 200 lbs	180 - 240 lbs	90 lbs
Bench or Pedestal Mounted	Yes	Yes	Yes	Yes	Stand	Yes	Yes	Yes

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®


Value Adding Accessories & Options

BELT
WIDTHS
1 1/2" TO 2"**1400 SERIES**


Internal Grinding Attachments
Convert Models 482 and
760 Grinders for
Internal Grinding.



- Small radius grinding
- Cavity grinding
- Hole grinding
- Quick installation, quick removal
- Increases standard belt length by 12"


**Radius and Internal Grinding**

A variety of interchangeable wheel sizes are available to allow tight radius and internal grinding.

INTERNAL & RADIUS ATTACHMENT

Description/ Stk Code	Belt Width	Wheel DIA." Options	Std. Whl. DxW
Fork Style/ 1400	1 1/2"	7/16, 5/8	7/16 x 3/8
Fork Style/ 1401	1"	9/16, 3/4, 1, 1 1/2	1 x 1
UNI Style/ 1401U	1"	9/16, 3/4, 1, 1 1/2	1 x 1
Close Access/ 1411	1"	9/16, 3/4, 1, 1 1/2	1 x 1
Fork Style/ 1402	2"	9/16, 3/4, 1, 1 1/2	1 x 2
Close Access/ 1412	2"	9/16, 3/4, 1, 1 1/2	1 x 2

Fits all Model 960 and 760 regardless of age.



See Accessory Arms



ACCESSORY ARMS

Value Adding Accessories & Options


Contact Arm #1453

Shown with
2"x1" Contact Wheel

Contact Arm #1470

Shown with
1"x.830" Contact Wheel

Contact Arm #1490

Shown with
1"x 1.830" Contact Wheel

Contact Arm #1423



Shown with 3/8" x 7/16" Contact Wheel



Wheel Diameters
from 3/8" to 3"

Wheel Widths
from 1/2" to 2"

Wheel Hardness
from 50 to 90
Duro

Wheels Plain
Faced/Serrated

Call Us For
Additional
Specifications
and Options

Contact Arm #1443

Shown with
1"x2" Contact Wheel

Contact Arm #1451

Shown with
1"x1" Contact Wheel

Contact Arm #1452

Shown with
3"x1" Contact Wheel

**INTERCHANGEABLE
ARMS FIT ALL
INTERNAL GRINDING
ATTACHMENTS**

BURR KING®

Value Adding Accessories & Options

PEDESTAL STANDS

Burr King heavy duty pedestals are designed to position grinding and polishing machines at a convenient operator height of 33". They must be securely bolted to the floor.

Adjustable pedestal. Easily change the pedestal height from 27" up to 37."

**VARI-SPEED MOTORS/ CONTROLLERS**

The variable speed motor option is available on all Burr King models. Surface speeds from 800 to 8000 S.F.P.M. are obtainable.

The variable speed motor controls temperature, cutting action, and finish to achieve desired results.

The adjustable speed motor controller supplies constant torque, has solid state controls, on/off switch, power light indicator with dial speed control.

**MAGNETIC STARTERS**

Magnetic starters provide low voltage and lost phase protection. They are recommended for all three phase machines. Magnetic starters protect motors from harmful currents, overloads, and excessive temperature rise. Machines may be ordered with a magnetic starter factory installed. Factory installed starters are securely bracket mounted or provided with an umbilical suitable for mounting the starter on a wall or post. Consult with the factory for the proper starter/motor and installation combination.

NOTE: Factory warranty may be voided if magnetic starter is not used with 3 phase models.



BURR KING®

Standard Features



70100 Shown

QUICK BELT CHANGE

The rear wheel quick change assembly makes belt changing a quick and simple operation. Lift handle and depress the button located in the center of the quick change knob, pull the handle forward to release tension, remove and replace the abrasive belt. The ratchet design of the quick change provides a positive and variable belt tension for loose belt and contour work.

BELT TRACKING ADJUSTMENT



70100 shown

SAFETY GUARDING

Burr King industrial grinders/buffers are fully guarded to protect pinch-points and unused portions of belt track areas. Guards permit easy access for rapid change of belts/discs and buffing wheels. Models 760 and 960 are shown



Model 760 (70100) shown with optional dust scoop for guarding.

Model 960 (95103) shown with safety door closed.



Positive tracking of the belt on the contact wheel is achieved by rotating the tracking knob to track belt left or right on the contact wheel while the machine is running. This patented device is easily accessible to the operator.


BURR KING®

Value Adding Accessories & Options




NARROW BELT GRINDING

The optional 702N "Narrow Wheel" uses a 1/2" x 60" abrasive belt, for tight radius and loose belt grinding.



NYLON WHEELS AND ADAPTERS

Wheel adapters are available in popular widths to economically convert your grinder to a nylon finishing machine capable of graining, polishing and deburring for special applications.



GRINDERS AND BUFFERS

Readily accepts flap, nylon, buffing, wire, and pneumatic wheels using inexpensive adapters.



WHEEL ADAPTERS

Accessories expand Burr King grinders and polishers.

BURR KING®

Standard Features

CONTACT WHEEL GRINDING



Contact wheel grinding is the most aggressive type of grinding and should be used when heavy stock removal is required. Each elastomer tired aluminum contact wheel is precision machined and balanced for smooth operation. It has been said, when compared to a bench grinder, "that grinding on a Burr King is like grinding on velvet."

The contact surface is bonded neoprene, available in 55 and 90 durometer with a plain or serrated face. Special narrow contact wheels are available.

Serrated contact wheels cut faster, run cooler, and give longer abrasive belt life. 2-hp to 3-hp motors are recommended when using these wheels for heavy stock removal.

CONTOUR AND LOOSE BELT GRINDING

The large throat clearance of the Burr King three wheel belt grinders provide large working area for contour and loose belt grinding, polishing, and deburring. Slack grinding and contact wheel grinding may be performed simultaneously with no special set-ups or down time.

BACKUP PLATEN AND WORKREST




The backup platen provides a large surface area for flat grinding and may be removed when not in use.

When backup platen is removed, contact wheel guard should be moved forward to guard pinch point.

The workrest is fully adjustable to any angle on the backup platen or contact wheel. It may be positioned below the contact wheel when not in use.

2-hp and 3-hp motors are recommended for use of backup platen for heavy stock removal.



BURR KING®

Value Adding Accessories & Options

CONTACT WHEELS



Grinders/buffers capability is readily expanded by selection of the best contact wheel/buffing wheel combination for your material. Many contact wheel diameters, widths, hardnesses and face geometries are available - 55 shore, for general purpose grinding, 90 shore serrated for heavy grinding. Numerous nylon wheels, buffing wheels and specialty wheels are available. Consult with the factory for proper selection.

ABRASIVE BELTS/DISCS



Abrasive belts and discs in various dimensions, grit types, and backing are available. Finishes from mirror to grain are possible. Material removal rates from slight to rapid and heavy are possible provided the proper abrasive, backing, surface speed, and equipment are selected. Consult with the factory for specific applications.

DUST COLLECTION SYSTEMS

BK 125 >**< BK 75****BK 100 >**

Burr King dust collectors use space saving cabinet design. All Burr King grinders/buffers may be coupled to these efficient dust collection systems. Select the BK 75 or BK 125 for portability or the BK100 for two grinder/buffer, fixed installation. Includes silencer and spark boxes. Machine sold separately.

DUST SCOOPS

Dust scoops are available for all Burr King models.

BURR KING®

MODEL 600



60100 shown
Wheel not included

The Model 600 and 800 machines provide fast and effective graining, finishing, deburring and surface conditioning. Designed to run nylon, flap, wire, and buffing wheels. Variable speed options extend the range and capability of the Model 600 and 800 machines. Composite, vitreous, and stone wheels are prohibited on the Model 600, and Model 800 and Burr King grinders.

Deburring & Polishing Machines

ACCESSORY WHEEL ADAPTERS



WA12

For wheels with 1/2" bore




WA14

Fits wheels up to
2" wide with 1-1/4" bore



WA1

Fits wheels 1" wide
with 1" bore



WA2

Fits wheels 2" wide
with 1" bore



MODEL 800



82100 shown

Model 800 shown equipped with optional variable speed. This option enables you to achieve many different types of finishes from graining to a high polish affect with one machine.
Also available with optional dust scoop. (Wheel not included)

**NOTE: CONSULT WITH FACTORY
FOR SPECIAL APPLICATIONS
AND ADAPTERS**

- Popular 6x1, 6x2, 8x1, 8x2 inch wheel options
- Quick wheel change
- Uses nylon, cotton, wire, fiber wheels
- Balanced, quiet, velvet smooth operation
- Up-front point of work
- Up to 4140 RPM spindle speed standard
- V-belt drive for efficient power transfer
- Pedestal or bench mount
- Compact footprint friendly to "cell" manufacturing
- Popular horse power options in popular voltages
- 50 hertz/motor/control options
- Variable speed 120/220-1 PH, and 220/440-3 HP options
- Sealed, long life bearings
- Rugged cast aluminum frame
- Precision machined and fabricated
- Full hood for dust collection
- OSHA compliant guarding
- UL/CSA listed electrical devices
- Burr King performance
- Burr King dependable!

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.


BURR KING®

MODEL 1000



Model 1000 takes 10" wheels. (Not included)

Shown with optional variable speed.



- Reliability of oversize "deep groove" ball bearings, fully shrouded and sealed for extended life
- Flexibility of bench or pedestal mounts
- Safety maximized by wheel guards with latching access doors
- Cleanliness maximized by an integrated dust shroud with dust outlet
- Expandable by the addition of magnetic starters
- Space saving compact size friendly to "cell manufacturing"
- Economy of minimal maintenance
- Full one year limited warranty

The Models 1000 and 1200 de-burrs, grains, polishes, cleans, de-scales, and buffs at a single station, a single machine, and a single operator.

- Convenient "up-front" wheel design takes the "difficult" out of "difficult to do parts"
- Convenient spindle position for speedy, comfortable operator transfer of parts wheel to wheel
- Versatility of convolute, flap, wire, fiber, nylon, or bristle-brush wheels
- Versatility enhanced by narrow and wide wheel capability mix and match wheel sizes and types
- Rugged, oversize, hardened and ground spindle with counter threaded 3/4" diameter wheel arbors
- Versatility of variable speed control options
- Work reducing horse power options
- Smooth "velvet touch" operation delivered by the precision you expect from Burr King
- Smooth, quiet "Micro-V" drive technology is operator friendly
- Durability of a cast aluminum frame

MODEL 1200

Uses 12" wheels.
(Not included)

(Pedestal included)

19610 shown

Shown with optional variable speed.




BURR KING®

11011 shown

Shown with optional variable speed and optional dust scoops. (Wheels not included)

BUFF AND POLISH WITH THE SAME MACHINE



11011 shown

Shown with optional variable speed. (Wheels not included)

MODEL 1001 VARIABLE SPEED POLISHING LATHE

After numerous requests, Burr King has answered the call once again with the M1001 Variable Speed Wide Polishing Lathe. The M1001 was based off of Burr King's top selling M1000 which features many of the same features found on the popular M1000.

Both machines will handle the most demanding polishing applications or for that extremely fine detailed work where only a variable speed Burr King will work.

By using an indirect drive system motor vibration is isolated to the motor, also vibration created by buffing wheels will be isolated from the motor resulting in longer bearing and motor life.

- Convenient "up-front" wheel design takes the "difficult" out of "difficult to do parts"
- Plenty of room between wheels almost 2 feet!
- 250-2500 RPM Variable Speed
- Versatility of convolute, flap, wire, fiber, nylon, or bristle-brush wheels
- Versatility enhanced by narrow and wide wheel capability mix and match wheel sizes and types
- Rugged, oversize threaded 3/4" diameter wheel arbors
- Versatility of variable speed control options
- Work reducing horse power options
- Smooth "velvet touch" operation delivered by the precision you expect from Burr King
- Smooth, quiet "Micro-V" drive technology is operator friendly
- Durability of a cast aluminum frame

The Burr King M1001 is designed for use with soft cloth or surface conditioning wheels (ScotchBrite®) only. Specific polishing applications may require additional installation of safety devices. Please consult with a safety engineer before use. Machine includes flanges and nuts, all wheels sold separately.

BURR KING®


MODEL 20 20" DISC GRINDER

Three versatile versions available in popular 3 phase, 60-hertz electronic options:

- Model 20 Disc Speed fixed at 1725 RPM
- Model 20B Fixed speed with a 10 ft. lb. mechanical disc brake
- Model 20VB Continuously adjustable from 200 to 1725 RPM with an adjustable electronic disc brake.

The Model 20 is:

- Precise enough for patternmakers
- The ideal tool to shape, flat grind, contour metal, wood and plastic
- Rapidly grinds and deburrs castings or fabricated parts
- Up to 9000 SFPM disc speed
- Reversible disc rotation
- Cast iron 3 horse power motor
- Rugged gray iron, ductile iron, and aluminum castings
- Miter gauge slide receiver
- Elevating Tilting Work Table
- Heavy Cast Iron/Aluminum Construction
- Premium Gears/Bearings Bushing
- Precision Machined/Balanced Solid Billet Disc
- Gear Driven Table Lift/Tilt
- Tilting Safety Guard
- Dust Scoop (DS-20) (Optional)
- Miter Attachment (MA-1) (Optional)



optional dust scoop



23100 shown

Disc is guaranteed to have face run out at less than 0.005 T.I.R.



RUGGED, DEPENDABLE, CAPABLE, LONG LASTING



29140 shown

MODEL 12 12" DISC GRINDER

Features:

- Rigid cast aluminum construction
- Cast iron table
- Precision billet aluminum disc
- Bench or pedestal mounted
- Forward/reversing switch
- Easy disc change with unique swing away feature

Options available:

- Variable speed, 3 phase motors & controls

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®

VibraKING Vibratory Chambers

VIBRATORY CHAMBERS THAT DELIVER QUIET, HIGH PERFORMANCE DEBURRING, POLISHING, DESCALING AND SURFACE CONDITIONING!

Optional process timers may be added to the M25, M45, and M85. These timers permit precise process timing control to manage critical finishes and economize valuable shop time. Process timers include high quality magnetic starter contactors.



45110 shown


Shown with FilterPAK 4001 and sound dampening lid.

- Capacity 2.5, 4.5 and 8.5 cubic feet
- Ultra Quiet
- High Energy, Fast Process Results
- Patented Drive and Isolation
- Portable
- Integrated, Metered, Compound Delivery System
- Flow-through Design
- Accepts Filter PAK 4001
- Replaceable Drain
- NEMA, UL, CSA, Listed Electricals
- Integrated Process Timer and/or Magnetic Starter Option

Let Burr King
Test Process
Your Parts.
-No Obligation
-Full Report
-FREE

- Amplitude fully adjustable
- Bronze caged, sealed long life bearings
- Rugged welded steel construction
- Heavy 85 duro urethane liner 5/8" thick
- Integrated discharge chute
- Compact footprint friendly to "cell" manufacturing
- OSHA compliant, enclosed guarding

Improved replaceable drains for models 25, 45, and 85.



- Quick to change
- Minimizes drain clogging
- Easy to reach
- Extends tub life
- Economical

- Standard on all VibraKING tubs



All Vibra King Chambers accept one to four dividers.




All Vibra King Chambers accept optional Vibra Hush lids reducing sound emission 3 to 6 db.



Optional magnetic starter with integrated timer. Available in single or three phase voltages.



Optional deflector, prevents flat parts from sticking to machine wall.


BURR KING®


All Burr King tubs or bowls
can be used wet or dry.



Vibra KING® with Hush Design

GENERAL DATA

	M25	M45	M85
Length max.in.	29	43	48
Width max in.	33	33	36
Height max in.	41	41	45
Total volume cu. ft.	2.5	4.5	8.5
Working volume cu.ft.	2.1	3.8	7.2
Tub depth, inside	15	15	20
Tub length, inside	20	35	37
Tub Width, inside	16	16	20
Max. part length, in.	19	34	36
Media load, lbs	150	250	450
Part load, lbs*	100	225	450
Weight max. lbs. (empty)	390	475	675
Horse power, standard	0.75 (1PH/3PH)	1.5 (1PH/3PH)	3.0 (3PH)

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®

- High Energy
- Power Cord & Switch
- Flow-Through Design
- Heavy Polymer Bowl
- Adjustable Amplitude (Except 110)



110
11000 shown



150
15000-1 shown




200
20000-1 shown

Burr King vibratory bowls are ideal for bench top polishing, descaling, deburring, and surface conditioning. Units are fast, quiet, and effective. Available in 3 qt, 10 qt, 20 qt, and 40 qt volumes.

SPECIFICATION CHART 110 • 150 • 200 • 15

Model	Working Capacity	HP	Adjustable Amplitude	Flow thru drain	Bowl Dimensions			
					A	B	C	D
110	3 qt	1/8	No	Yes	10"	3.25"	4.25"	7.25"
150	10 qt.	1/5	YES	YES	15"	5.5"	5.75"	10.5"
200	20 qt.	1/5	YES	YES	17"	6.5"	6.5"	13"
M15	40 qt.	1/2	YES	YES	21.5"	7"	8.5"	17.25"



MODEL 110:
OVERALL MACHINE HEIGHT = 13"
DIAMETER = 10"
LOAD MAX POUNDS: 10

MODEL 150:
OVERALL MACHINE HEIGHT = 17 1/2"
DIAMETER = 15"
LOAD MAX POUNDS: 35

MODEL 200:
OVERALL MACHINE HEIGHT = 19 1/2"
DIAMETER = 17"
LOAD MAX POUNDS: 50

MODEL 15:
OVERALL MACHINE HEIGHT = 28"
DIAMETER = 24"
LOAD MAX POUNDS: 150

BURR KING®

VIBRA KING 15

The M15 offers the same reliability and options as our smaller bowls but with more power and larger capacity. The M15 comes complete with stand and timer.

GENERAL DATA

Height max inches	40"
Width max inches	22"
Depth max inches	23"
Total volume cu. feet	1.3
Working volume cu. feet	1.0
Bowl diameter, inside inches	17.5"
Bowl depth inside	9.5"
Part length max. inches	12"
Part width max. inches	5.5"
Load max. lbs.	150
Horse power	1/2
RPM	1725
Volt/Phase	115/1



Media Discharge Chute >



15110 shown

FLEXIBLE

- Adjustable amplitude
- Ceramic, plastic, burnish, wood and shell capable for wet or dry processing
- Adapts to FilterPAK 4001 & SumpPAK 1000 filtration systems with flow through design
- Dual outlet integrates with timer to adapt accessories
- Timer Controlled, 0-6 hours

RELIABLE

- Heavy polymer bowl
- Replaceable drain
- Durable coated metal surfaces

LABOR REDUCTION

- Quick media discharge chute

CONFIDENCE/SAFETY

- UL/CSA listed motors, controls and wiring
- Fully shrouded mechanical section
- One year conditional warranty
- American designed and manufactured in Warsaw, MO
- Backed by Burr King's promise of performance and dependability

OPERATOR/SHOP FRIENDLY

- Cell Manufacturing friendly
- Portability of no bolt down operation

FASTER PROCESSING

- High energy

BURR KING®

VIBRA KING 40 DELIVERS FAST, QUIET, HIGH PERFORMANCE DE-BURRING, POLISHING, BURNISHING, DE-SCALING, AND SURFACE CONDITIONING.



44200 shown

VIBRA KING 40

FLEXIBLE

- Ceramic, plastic, burnish, wood and shell capable for wet or dry processing
- Adapts to FilterPAK 4001 filtration system
- Adapts to common compound dosing systems
- Integrated into optional PLC remote/local control
- Standard 1" screen hole, Other sizes available: 1/2", 1-3/8", custom screens can also be made.

RELIABLE

- Replaceable drain
- Steel reinforced, heavy urethane encapsulated tub
- Durable coated metal surfaces
- Stress proof drive shaft
- Double row roller bearings with grease fittings

CONFIDENCE/SAFETY

- UL/CSA listed motors, controls and wiring
- Fully shrouded mechanical section
- One year conditional warranty
- American designed and manufactured in Warsaw, MO
- Backed by Burr King's promise of performance and dependability

OPERATOR/SHOP FRIENDLY

- Noise level below 85db (media load dependent)

FASTER PROCESSING

- High energy vibratory rate, up to 2500 pulses per second (PPS)

LABOR REDUCTION

- Variable speed controls available for quick individual part set-up
- Quick media discharge chute
- Quick separating screen changes

GENERAL DATA

Width max Inches	52
Front to back max. inches	36
Height max inches	42
Total volume cu. feet	4.0
Working volume cu. feet	2.2
Tub diameter, inside inches	30.25
Tub height, inside inches	11.25
Part length max. inches	16
Part width max. inches	4
Tray height minimum	34
Chute height minimum	21
Load max. pounds, combined media plus parts	350
Weight max. empty pounds	750
Floor required	concrete or other suitable
Horse Power	2.0 (1.8kw)




BURR KING®

VibraKING Vibratory Bowls & Accessories



Vibratory bowl not included.

STANDPAK 5000

The perfect mate
for Burr King
Vibratory Bowls

- Accepts FilterPak 4001
- 0-6 Hour Process Timer
- Timer Controlled AC outlets
- Isolator Stance
- Steel Construction
- Improves action
- Space Saving 16"x20"x21"
- Power Cord & Plug 110V,
- Mass finish many different material types, part shapes
- Perfect bench-top small mass finishing system
- Quiet operation
- Compatible with most media styles
- Compact footprint friendly to "cell" manufacturing



Mount your
VibraKING Bowl on
the StandPAK 5000,
add a FilterPak 4001
for a complete,
timer controlled,
filtered, compound
finishing system.

SUMPPAK 1000

The SumpPAK 1000 comes with a 5 gallon bucket, pump hanger, pump and all tubes to connect filtration system to machine. Can be used with bowls or tubs.



FILTERPAK 4001

The FilterPAK 4001 can be used with vibratory bowls or tubs. Heavy duty Polyethylene construction with single submersible pump and disposable filter bag. 10 gallon capacity. Also available FilterPAK 8000 used only with Vibra KING 85, stainless steel construction.

- Continuous fluid filtration
- Traps and holds sludge and debris in inexpensive, easily disposable filters
- Cleaner compounds results in cleaner parts
- Superior finishes and shorter cycle times with a filtered system
- Significantly reduces shop mess
- Filtration from 5 to 100 micron
- Filter change less than 2 minutes
- 115 VAC 140 GPH Pump
- 10 Gallon plus capacity
- Heavy duty Polyethylene
- Space saving 12"x14"x15"
- Dual Chamber



Vibratory Media & Accessories

Various media is available for processing ferrous, non-ferrous, plastics, and other materials. Finishes from sparkling clear to matte are possible with the proper selection of media and compounds. Specialty medias include ceramic, synthetic, plastics, cobs, shells, etc. Consult with the factory for the best media for your application.



Note: You can request our separate media sheet

MEDIA SELECTION GUIDE

- Size and coarseness of media may be substituted for stated media. Consult with the factory.
- Choose ceramic media for faster finishing and uniform matte finish.
- Choose plastic media for low RMS finishes and pre-plate finish.
- Larger media yields faster finishing and coarser finish. Smaller media yields slower finishing and finer finish.
- Media coarseness: P-20 most coarse; P-40 medium coarse; P-60 burnishing
- Non-abrasive, burnishing media and compounds are available. Consult with the factory.
- Other media forms, composition, and coarseness are also available. Consult with the factory.
- BKS-60 low suds soap for most non ferrous applications.
- AR-60 low suds soap with anti-rust for most ferrous applications. Provides temporary rust protection.



Magnets for retrieving small ferrous metal parts from media

Media/Parts Separating Screens and container



The factory will test process your parts to assist in good media/compound selection for your parts. Send part samples, receive back a no cost written report recommending media/compounds/equipment.

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.

BURR KING®

Important Safety Information

All Burr King products are built to deliver excellent performance and reliability. Our products are designed and manufactured to meet applicable safety requirements. In order that our customers realize the maximum benefit possible from our products, our primary concern is that they understand, and use, proper and safe procedures. The following list of general safety instructions is the minimum applicable to all Burr King products. For detailed operating and safety instructions see the applicable "Operating Instructions" for the specific Burr King product.

Occupational Noise Exposure

Burr King products produce levels of noise consistent with their intended purposes. The level and spectral content of noise produced is dependent on the equipment size, the degree that the equipment is maintained in proper operating condition, the abrasive/media and accessories used, the specific application, use of options, and the surrounding environment. Noise levels produced by various Burr King models, as measured at the Burr King factory, range from 72 to 91 decibels. Product operators and persons in the immediate product vicinity should be protected from excessive noise levels as prescribed in OSHA regulation 29, part 1910.95 titled "Occupational Noise Exposure".

Product Warranty

Burr King Manufacturing Company, Inc. warrants its products to be free of defects in material and workmanship. The period of this warranty is 1 year (90 days for vibratory bowls of 20 quart and lesser volume) from the date of purchase. No warranty is provided for products that have been modified, abused, handled carelessly, where repairs have been made or attempted by others, or for freight damage. No warranty is provided for three phase electric motors, controllers, etc. when the motors, controllers are not protected by magnetic starters that were supplied and installed by Burr King Manufacturing Company, Inc. No other warranty, written or verbal is authorized by Burr King Manufacturing Company, Inc.

During the warranty period Burr King Manufacturing Company, Inc. (or its authorized suppliers or agents) will replace or repair a product without charge if the product is found by Burr King Manufacturing Company, Inc. to be defective. To receive warranty service you must contact Burr King Manufacturing Company, Inc. and receive authorization for warranty service. Unless otherwise authorized by Burr King Manufacturing Company, Inc. products must be returned to the factory to receive warranty service. Third party Burr King suppliers may provide warranty service for electric motors, pumps, and other accessories.

For the first thirty days after purchase, and when Burr King authorizes warranty service, we will pay normal and necessary freight charges both ways. After thirty days the customer is responsible for all freight charges. Where possible Burr King Manufacturing Company Inc. may elect to make on site service and/or repairs necessary to return the product to serviceable condition. Our priority at all times is to satisfy our customers.

All rotating equipment can be hazardous if not properly used and maintained. Burr King Manufacturing encourages its customers to:

1. Read and understand all operating instructions.
2. Train all operators and others in the work area in these and other safe practices.
3. Securely bolt the machine to a solid work surface.
4. Observe National Electric Codes, state and local codes for all electrical wiring and connections.
5. Keep guards and other safety apparatus functional and in-place
6. Adjust the work rest (if any) such that the gap between the moving abrasive and the work rest is less than 1/8 inch., and never acute to the belt.
7. Avoid wearing loose clothing, long hair, or other garb that may become entangled in moving machinery.
8. Use holding devices such that work pieces are not grabbed, or ejected by wheels or moving abrasive belts, disks, wheels, etc.
9. Never allow pointed work pieces to be handled or held in such a way that they could be grabbed by the moving belt, disk, or wheel and forcibly propelled toward the operator or any bystanders.
10. Use appropriate eye, face, head, body, hand, arm, leg, foot protection for operators and other persons in the work area.
11. Keep the work area free of trip points and other physical hazards.
12. Use suitable inhalation protection.
13. Keep alloys separate to avoid possible combustion risks.
14. Know if the materials to be worked on can create a fire, combustion, or toxic hazard, treat them accordingly, in a safe manner, according to local codes and ordinance.
15. Use no water or other electrically conductive fluid unless your machine has been specifically designed for wet use (NEMA 4,4X)
16. Disconnect power before performing maintenance, changing abrasive devices, or otherwise entering the workings of the machine.
17. Maintain the machine in specification compliant and safe operating condition.
18. Post these and other pertinent safety instructions.



License Plate Frames



Custom Car Fabrication



Shoes

ALWAYS WEAR PROTECTIVE EYE, FACE, ARM, LEG AND BODY GEAR WHEN USING ANY GRINDER, POLISHER, BUFFER OR OTHER ROTATING MACHINERY.



CALL FOR A FREE DEMO—WE'LL COME TO YOU

Burr King's factory trained representatives can come directly to your location and give you a hands-on demonstration. This is a great opportunity to experience the "Velvet Touch" only a Burr King can provide. Call today!

800-621-2748

INDUSTRIES SERVED

**MOTORCYCLES • TRAINS • GOLF CLUBS • LAWN EQUIPMENT
 TRACTORS • POLICE CARS • GOLF CARTS • GUNS
 KNIVES • SHOES • ORTHOTICS • MUFFLERS • WELDING
 FIRE DEPARTMENT • LICENSE PLATE FRAMES • HORSE
 SHOES • CHOPPERS • ORGANS • DIE CAST • HOT RODS
 AEROSPACE • WHEELS • BOATS • GUITARS • RACE CARS
 PAINT BALL GUNS • JEWELRY • FURNITURE • BAKE WEAR
 WOODWORKING • TOOL BOXES • HAND TOOLS • TRUCK
 BODIES • OIL FIELD EQUIPMENT • ROBOTIC PRODUCTION
 AGRICULTURE • EXERCISE EQUIPMENT • ENGRAVING
 MOVIE PROPS • THEME PARKS • DENTAL EQUIPMENT
 BARBECUES • MEDICAL INSTRUMENTS • HOME APPLIANCES
 OFF ROAD EQUIPMENT • CONSTRUCTION EQUIPMENT
 POWDER COATING • WATER ENTERTAINMENT • EDUCATION
 PROSTHETICS • TACKLE • RESTAURANT EQUIPMENT
 OPTICAL • COMMUNICATION HEADSETS • HIGH ALTITUDE
 SUITS AND HELMETS • SNOW PLOWS • MUSEUMS • LADDERS
 LIGHTING • SPORTS EQUIPMENT • SURGICAL INSTRUMENTS
 SPECIALTY TRAILERS • MODEL BUILDING • SCULPTURE
 MILITARY DECOYS • SHIP BUILDING • THEATRICAL EQUIPMENT
 GLASS LAMINATION • PRINTING MACHINERY • LANDSCAPE
 HYDROPOWER MAINTENANCE • FIREPLACE ACCESSORIES
 CHROME AND NICKEL PLATING • PAPER MILL MAINTENANCE
 IN FLIGHT FOOD SERVICE EQUIPMENT • CERAMIC MFG.**